


BIRCOcanal | NW 300

The Supply Channel for Heavy Duty Areas

Supply channels with angles | cast-in mounting rails

- + With hot-dipped galvanised solid steel angles for combi-closure system
- + Safety sealing joint
- + Cast-in mounting rails type 28/15, hot-dipped galvanised



Description	Length	External dimension Width/Construction height	Internal dimension Width/Height	Weight	Load class DIN EN 1433	Article No.
Supply channel	1000 mm	450/470 mm	300/350 mm	223.6 kg	A 15 – F 900	052310
Supply channel	2000 mm	450/470 mm	300/350 mm	446.0 kg	A 15 – F 900	052320

Supply channels with angles | without cast-in mounting rails

- + With hot-dipped galvanised solid steel angles for combi-closure system
- + Safety sealing joint

Description	Length	External dimension Width/Construction height	Internal dimension Width/Height	Weight	Load class DIN EN 1433	Article No.
Supply channel	1000 mm	450/470 mm	300/350 mm	221.0 kg	A 15 – F 900	052330
Supply channel	2000 mm	450/470 mm	300/350 mm	437.6 kg	A 15 – F 900	052340

Bulb ductile iron covers | for supply channels with angles

- + Solid
- + Black immersion-lacquered or galvanised
- + 8 point per metre M16/A2 bolt connection
- + 8 point per metre Easylock-fastening (alternatively)




Description	Length	Width	Height	Weight	Load class DIN EN 1433	Article No.
black	500 mm	437 mm	45 mm	32.1 kg	A 15 – E 600	052376/e
galvanised	500 mm	437 mm	45 mm	31.0 kg	A 15 – E 600	052376v/e

Article No. with v = galvanised, Article No. with e = with Easylock
Exception up to D 400: Not for use across the carriage- way of highways or motorways.



Supply channels without angles | cast-in mounting rails

- + Safety sealing joint
- + Cast-in mounting rails type 28/15, hot-dipped galvanised



Description	Length	External dimension Width/Construction height	Internal dimension Width/Height	Weight	Load class DIN EN 1433	Article No.
Supply channel	1000 mm	450/415 mm	300/340 mm	212.0 kg	A 15 – E 600	050310
Supply channel	2000 mm	450/415 mm	300/340 mm	422.0 kg	A 15 – E 600	050320

Supply channels without angles | without cast-in mounting rails

- + Safety sealing joint

Description	Length	External dimension Width/Construction height	Internal dimension Width/Height	Weight	Load class DIN EN 1433	Article No.
Supply channel	1000 mm	450/415 mm	300/340 mm	211.0 kg	A 15 – E 600	050330
Supply channel	2000 mm	450/415 mm	300/340 mm	417.0 kg	A 15 – E 600	050340

Reinforced concrete cover | for supply channels without angles

- + Smoothed surface
- + 2 cast-in anchor sleeves RD 12 for mechanical installation



Description	Length	Width	Height	Weight	Load class	Article No.
Reinforced concrete cover	1000 mm	450 mm	100 mm	122.0 kg	SLW 60	050398

[!] Please ensure that a sealing tape is generally stuck down between BIRCOcanal and the reinforced concrete cover.

BIRCOcanal | Accessories

- + Different accessories for BIRCOcanal are listed on page 99.

Exception up to D 400: Not for use across the carriage- way of highways or motorways.