


# BIRCOtop | Series F 210

Optimum building façade drainage in fixed construction height

Channel elements | without visible edge | perforated on one side


- + Galvanised
- + Also available in stainless steel (V2A)
- + Bolt connection bar



Description	Length	Width	Construction height	Weight	Load class	Article no.
Construction height 1, galvanised	500 mm	210 mm	50 mm	1.4 kg	walkable	074421
Construction height 1, galvanised	1000 mm	210 mm	50 mm	2.8 kg	walkable	074422
Construction height 1, galvanised	3000 mm	210 mm	50 mm	8.5 kg	walkable	074424
Construction height 2, galvanised	500 mm	210 mm	75 mm	1.6 kg	walkable	074431
Construction height 2, galvanised	1000 mm	210 mm	75 mm	3.2 kg	walkable	074432
Construction height 2, galvanised	3000 mm	210 mm	75 mm	9.6 kg	walkable	074434

## End caps

- + Also available in stainless steel (V2A)



Description	Width	for construction height	Weight	Load class	Article no.
End cap, galvanised, construction height 1	183 mm	50 mm	0.1 kg	walkable	074441
End cap, galvanised, construction height 2	183 mm	75 mm	0.1 kg	walkable	074442

## Mesh gratings

- + Galvanised
- + Also available in stainless steel (V2A)
- + 2 point per metre M12A2 bolt connection



Description	Length	Width	Height	Weight	Inlet opening	Inlet cross section	Load class	Article no.
galvanised	500 mm	200 mm	20 mm	2.3 kg	MW 30/10 mm	1484 cm <sup>2</sup> /m	walkable	074461
galvanised	1000 mm	200 mm	20 mm	4.4 kg	MW 30/10 mm	1484 cm <sup>2</sup> /m	walkable	074451
galvanised	500 mm	200 mm	20 mm	3.6 kg	MW 30/15 mm	1398 cm <sup>2</sup> /m	walkable	074462
galvanised	1000 mm	200 mm	20 mm	7.1 kg	MW 30/15 mm	1398 cm <sup>2</sup> /m	walkable	074452

MW = mesh width